

## Monaco SunReel & Monaco SunReel Extra Specification Sheet

1 x 316 Stainless Steel enclosure 300 x 150 x 80mm, vented, IP66 rated. Can be turned into the sun for optimum solar gain.
Operated by 3-way key switch, IP65 rated.  SunReel Extra models can also be operated by remote control fob.
1 x 2 pole connection point for charger, IP67 rated. 1 x 4 pole connection point for power to motor, IP67 rated 1 x panel vent, IP67 rated.
2 x rechargeable in-line batteries Leoch 12v 4.5Ah (T1) (giving 9 amps in total).
1 x Solar Panel 18V 4W framed, 260mm x 155, monocrystalline.
R35/8G 12v DC motor 35Nm 8rpm. Manufactured in Germany.
Separate instruction manual supplied with the Reel.
12V 0.8A 6 Stage Charger, fully automated charging cycle, IP65 rated. Comes with 3m cable for safety.
Not supplied with Monaco SunReel unless requested as an additional requirement. C/w Monaco SunReel Extra as standard.
Up to 15m long (max. length)
To connect the Solar pack to the electric motor if the solar pack is
to be sited away from the reel i.e. for indoor pools or outdoor pools where solar gain will be minimised because of obstructing buildings or trees.